

# T2/S

■ Cricco pneumatico a due punti di alzata ultraribassato

■ Two-arm pneumatic jack extremely low

■ Pneumatischer achsabheber mit 2 - Punktauflage sehr flach

■ Cric pneumatique à deux points d'élevement très bas

■ Gato neumático con dos puntos de apoyo ultrarebajado

■ Applicabile sui seguenti ponti:  
Applicable on the following lifts:

Anwendbar auf folgenden Hebebühnen:

Applicable sur les ponts éleveurs suivants:

Applicable sobre los elevadores siguientes:

• VIVA 50

• KAR 45

• STAR 45

• FOX 45

• STEALTH 40 VXB



Capacità Capacity Tragkraft Capacité Capacidad	Pressione aria Air pressure Luftdruck Pression d'air Presion de aire	Altezza minima Min. height Min. Hubhöhe Min hauteur Altura minima	Corsa Travel Effektiver Hub Course Recorrido	Lunghezza totale Overall length Gesamtlänge Longueur tot. Largo total	Larghezza Width Breite Largeur Anchura
2000 kg	8,5 - 12	180 mm	295 mm	1440 mm	850 - 1010 mm

## T2/S

- REGISTRABILE
- ADJUSTABLE
- AUSDEHNBAR
- ADAPTABLE
- ADAPTABLE

